




GR-750XL-2

75 Ton Capacity (68 Metric Tons)

HYDRAULIC ROUGH TERRAIN CRANE

DIMENSIONS



Note : Dimension is with boom angle at -1.6 degree.

GENERAL DIMENSIONS (29.5 - 25 Tires)

	Feet	Meters
Turning radius		
4 wheel steer	22' 4"	6.8
2 wheel steer	39' 1"	11.9
Tail swing of counterweight	13' 9"	4.19

Specifications are subject to change without notice.

CRANE SPECIFICATIONS

BOOM

Five section full power synchronized telescoping boom, 36.1'~141.1' (11.0m~43.0m), of round box construction with six sheaves, 17-5/16" (0.44m) root diameter, at boom head. The synchronization system consists of two telescope cylinders, an extension cable and retraction cable. Hydraulic cylinder fitted with holding valve. Two easily removable wire rope guards, rope dead end provided on both sides of boom head. Boom telescope sections are supported by wear pads both vertically and horizontally. Extension speed 105' in 128 seconds.

BOOM ELEVATION - By a double acting hydraulic cylinder with holding valve. Elevation -1.6 ° ~80.3 °, combination controls for hand or foot operation. Boom angle indicator.

Automatic speed reduction and soft stop function.

Boom raising speed 20 ° to 60 ° in 46 sec.

JIB - Two stage bi-fold lattice type with 3.5 °, 25 ° or 45 ° offset (tilt type). Single sheave, 15-5/8" (0.396m) root diameter, at the head of both jib sections. Stored alongside base boom section. Jib length is 33.2' (10.1m) or 58.1' (17.7m). Assistant cylinders for mounting and stowing, controlled at right side of superstructure. Self stowing jib mounting pins.

AUXILIARY LIFTING SHEAVE (SINGLE TOP)

Single sheave, 15-5/8" (0.396m) root diameter. Mounted to main boom head for single line work (stowable).

ANTI-TWO BLOCK - Pendant type over-winding cut out device with audio-visual (FAILURE lamp/BUZZER) warning system.

SWING

Hydraulic axial piston motor through planetary swing speed reducer. Continuous 360 ° full circle swing on ball bearing turn table at 2.4min⁻¹{rpm}. Equipped with manually locked/released swing brake. A 360 ° positive swing lock for pick and carry and travel modes, manually engaged in cab. Twin swing system: Free swing or lock swing controlled by selector switch on front console.

HOIST

MAIN HOIST - Variable speed type with grooved drum driven by hydraulic axial piston motor through speed reducer. Power load lowering and raising. Equipped with automatic brake (neutral brake) and counterbalance valve. Controlled independently of auxiliary hoist. Equipped with cable follower and drum rotation indicator.

DRUM - Grooved 15-3/4" (0.40m) root diameter x 23-9/16" (0.599m) wide. Wire rope: 771' of 3/4" diameter rope (235m of 19mm). Drum capacity: 1,074' (327.5m) 7 layers. Maximum single line pull: 1st layer 15,200 lbs (6,880kg). Maximum permissible line pull wire strength: 15,600 lbs (7,085kg).

AUXILIARY HOIST - Variable speed type with grooved drum driven by hydraulic axial piston motor through speed reducer. Power load lowering and raising. Equipped with automatic brake (neutral brake) and counterbalance valve. Controlled independently of main hoist. Equipped with cable follower and drum rotation indicator.

DRUM - Grooved 15-3/4" (0.40m) root diameter x 23-9/16" (0.559m) wide. Wire rope: 436' of 3/4" diameter rope (133m of 19mm). Drum capacity: 1,074' (327.5m) 7 layers. Maximum single line pull: 1st layer 15,200 lbs (6,880kg). Maximum permissible line pull wire strength: 15,600 lbs (7,085kg).

WIRE ROPE - Warrington seal wire, extra improved plow steel, preformed, independent wire rope core, right regular lay. 3/4" (19 mm) 6x31 class

HOOK BLOCKS

75 ton (68 metric ton) - 7 sheaves with swivel hook block and safety latch.
6.2 ton (5.6 metric ton) - Weighted hook ball with swivel and safety latch.

HYDRAULIC SYSTEM

PUMPS - Two variable piston pumps for crane functions. Tandem gear pump for steering, swing and optional equipment. Powered by carrier engine. Pump disconnect for crane is engaged/disengaged by rotary switch from operator's cab.

CONTROL VALVES - Multiple valves actuated by pilot pressure with integral pressure relief valves.

RESERVOIR - 222 gallon (840 lit.) capacity. External sight level gauge.

FILTRATION - BETA10=10 return filter, full flow with bypass protection, located inside of hydraulic reservoir. Accessible for easy replacement.

OIL COOLER -Air cooled fan type.

CAB AND CONTROLS

Both crane and drive operations can be performed from one cab mounted on rotating superstructure.

Left side, 1 man type, steel construction with sliding door access and safety glass windows opening at side. Door window is powered control. Windshield glass window and roof glass window are shatter-resistant. Tilt-telescoping steering wheel. Adjustable control lever stands for swing, boom elevating, boom telescoping, auxiliary hoist and main hoist. Control lever stands can change neutral positions and tilt for easy access to cab. 3 way adjustable operator's seat with high back, headrest and armrest. Engine throttle knob. Foot operated controls: boom elevating, boom telescoping, service brake and engine throttle. Hot water cab heater and air conditioning.

Dash-mounted engine start/stop, monitor lamps, cigarette lighter, drive selector switch, parking brake switch, steering mode select switch, power window switch, pump engaged/disengaged switch, swing brake switch, telescoping/auxiliary hoist select switch, outrigger controls, free swing / lock swing selector switch, eco mode switch and ashtray.

Instruments - Torque converter oil temperature, engine water temperature, air pressure, fuel, speedometer, tachometer, hour meter and odometer / tripmeter. Hydraulic oil pressure is monitored and displayed on the AML-C display panel.

Tadano electronic LOAD MOMENT INDICATOR system (AML-C) including:

- Control lever lockout function
- Boom position indicator
- Outrigger state indicator
- Boom angle / boom length / jib offset angle / jib length / load radius / rated lifting capacities / actual loads read out
- Ratio of actual load moment to rated load moment indication
- Automatic Speed Reduction and Slow Stop function on boom elevation and swing
- Working condition register switch
- Load radius / boom angle / tip height / swing range preset function
- External warning lamp
- Tare function
- Fuel consumption monitor
- Main hoist / auxiliary hoist select
- Drum rotation indicator (audible and visible type) main and auxiliary hoist

TADANO AML-C monitors outrigger extended length and automatically programs the corresponding "RATED LIFTING CAPACITIES" table

Operator's right hand console includes transmission gear selector and sight level bubble. Upper console includes working light switch, roof washer and wiper switch emergency outrigger set up key switch, jib equipped/removed select switch, eco mode switch, boom emergency telescoping switch (2nd / 3rd, 4th and top) and air conditioning control switch. Swing lock lever.

NOTE: Each crane motion speed is based on unladen conditions.

CARRIER SPECIFICATIONS

TYPE - Rear engine, left hand steering, driving axle 2-way selected type by manual switch, 4x2 front drive, 4x4 front and rear drive.

FRAME - High tensile steel, all welded mono-box construction.

TRANSMISSION - Electronically controlled full automatic transmission. Torque converter driving full powershift with driving axle selector. 6 forward and 2 reverse speeds, constant mesh.

- 3 speeds - high range - 2 wheel drive; 4 wheel drive
- 3 speeds - low range - 4 wheel drive

TRAVEL SPEED - 22 mph (36 km/h)

AXLE - Front: Full floating type, steering and driving axle with planetary reduction. Rear: Full floating type, steering and driving axle with planetary reduction and non-spin rear differential.

STEERING- Hydraulic power steering controlled by steering wheel. Four steering modes available: 2 wheel front, 2 wheel rear, 4 wheel coordinated and 4 wheel crab .

SUSPENSION - Front: Rigid mounted to frame.

Rear: Pivot mounted with hydraulic lockout device.

BRAKE SYSTEMS - Service: Air over hydraulic disc brakes on all 4 wheels. Parking/Emergency: Spring applied-air released brake acting on input shaft of front axle. Auxiliary: Electro-pneumatic operated exhaust brake.

TIRES - 29.5-25 22PR(OR) or 29.5-25 28PR(OR)

OUTRIGGERS - Four hydraulic, beam and jack outriggers. Vertical jack cylinders equipped with integral holding valve. Each outrigger beam and jack is controlled independently from cab. Beams extend to 23' 11-3/8" (7.3 m) center-line and retract to within 10' 10-1/2" (3.315 m) overall width with floats. Outrigger jack floats are attached thus eliminating the need of manually attaching and detaching them. Controls and sight bubble located in superstructure cab. Four outrigger extension lengths are provided with corresponding "RATED LIFTING CAPACITIES" for crane duty in confined areas.

Min. Extension	8' 10-1/4" (2.7m) center to center
Mid. Extension	18' 1/2" (5.5m) center to center
Mid. Extension	21' 11-3/4" (6.7m) center to center
Max. Extension	23' 11-3/8" (7.3m) center to center
Float size(Diameter)	1' 11- 5/8" (0.6m)

ENGINE

Type	Cummins QSB6.7 [Tier 4]
No. of cylinders	Direct injection diesel
Combustion	6
BoreXStroke, in.(mm)	4 cycle, turbo charged and after cooled
Displacement, cu. in (liters)	400.8 (6.620) 4.882 (107 x 124)
Air inlet heater	24 volt preheat
Air cleaner	Dry type, replaceable element
Oil filter	Full flow with replaceable element
Fuel filter	Full flow with replaceable element
Fuel tank, gal.(liters)	79.2 (300), right side of carrier
Cooling	Liquid pressurized, recirculating by-pass

Radiator	Fin and tube core, thermostat controlled
Fan, in.(mm)	Suction type, 9-blade, 28 (711) dia.
Starting	24 volt
Charging	24 volt system, negative ground
Battery	2-120 amp. Hour
Compressor, air, CFM(l /min)	17.0 CFM (481) at 2,400rpm
Horsepower (kW)	Gross 260 (194) at 2,500rpm
Torque, Max. ft-lb (Nm)	622 (843) at 1,600rpm
Capacity, gal.(liters)	
Cooling water	2.7 (10)
Lubrication	4.0 (15)
Fuel	79.2 (300)

STANDARD EQUIPMENT

- Five section full power partially synchronized boom
36.1'~141.1' (11.0 m~43.0 m)
- 33.2' or 58.1' (10.1 m or 17.7 m) bi-fold lattice jib (tilt type)
with 3.5 °, 25 ° or 45 ° pinned offsets and self storing pins.
- Auxiliary lifting sheave (single top) stowable
- Variable speed main hoist with grooved drum, cable follower
and 771' of 3/4" cable.
- Variable speed auxiliary hoist with grooved drum, cable follower
and 436' of 3/4" cable.
- Drum rotation indicator (audible,visible and thumper type) main
and auxiliary hoist
- Anti-Two block device (overwind cutout)
- Boom angle indicator
- Tadano electronic load moment indicator system (AML-C) -
Outrigger extension length detector
- Electronic crane monitoring system
- Tadano twin swing system and 360 ° positive swing lock
- Self centering finger control levers with pilot control -Control
pedals for boom elevating and boom telescoping -3 way
adjustable cloth seat with armrests, high back
and seat belt
- Tilt-telescoping steering wheel
- Tinted safety glass and sun visor
- Front windshield wiper and washer
- Roof window wiper and washer
- Power window (cab door)
- Rear view mirrors (right and left side)
- Mirror for main and auxiliary hoists
- Cigarette lighter and ashtray
- Cab floor mat
- Pump disconnect in operator's cab
- Hydraulic oil cooler
- Hot water cab heater and air conditioner
- Positive control
- Quick reeving type bi-fold jib
- Work lights
- Independently controlled outriggers
- Four outrigger extension positions
- Self-storing outrigger pads
- Cummins QSB6.7 turbo charged
after cooled engine (260HP) with exhaust brake
- Electronic controlled automatic transmission driven
by torque converter
- 4 X 4 X 4 drive/steer
- Non-spin rear differential
- Automatic rear axle oscillation lockout system
- 29.5-25 22PR(OR) tires or 29.5-25 28PR(OR) tires
- Disc brakes
- Fenders
- Air dryer
- Water separator with filter(high filtration)
- Engine over-run alarm
- Back-up alarm
- Low oil pressure/high water temp. warning device (visual)
- Rear steer centering light
- Air cleaner dust indicator
- Full instrumentation package
- Complete highway light package
- Tool storage compartment
- Tire inflation kit
- 24 volt electric system
- 6.2 ton (5.6 metric ton) hook ball with swivel
- 75 ton (68 metric ton) - 7 sheaves with swivel hook block

and safety latch for 3/4"(19mm) wire rope
- Towing hooks-Front and rear
- Lifting eyes
- Hook block tie down (front bumper)
- Weighted hook storage compartment
- Halogen head lamp
- Telematics (machine data logging and monitoring system)
with HELLO-NET via internet
- Fuel consumption monitor
- Eco mode system

HOISTING PERFORMANCE

LINE SPEEDS AND PULLS

Layer	Main or auxiliary hoist - 15'-3/4" (0.4m) drum			
	Linespeeds ¹		Line pulls Available ²	
	F.P.M.	m/min	Lbs.	kgf
1st	358	109	15,200	6,880
2nd	387	118	13,900	6,310
3rd	417	127	12,800	5,820
4th	446	136	11,900	5,410
5th	475	144	11,100	5,050
6th	504	153	10,400	4,730
7th ³	533	162	9,800	4,460

¹ Line speeds based only on hook block, not loaded.

² Developed by machinery with each layer of wire rope, but not based on rope strength or other limitation in machinery or equipment.

³ Seventh layer of wire rope are not recommended for hoisting operations.

DRUM WIRE ROPE CAPACITIES





Wire rope layer	Main and auxiliary drum grooved lagging 3/4" (19mm) wire rope			
	Rope per layer		Total wire rope	
	Feet	Meters	Feet	Meters
1	123.3	37.6	123.3	37.6
2	133.5	40.7	256.8	78.3
3	143.3	43.7	400.2	122.0
4	153.5	46.8	553.8	168.8
5	163.3	49.8	717.1	218.6
6	173.8	53.0	891.0	271.6
7	183.3	55.9	1074.4	327.5

DRUM DIMENSIONS


	Inch	mm
Root diameter	15-3/4"	400
Length	23-9/16"	599
Flange diameter	27-3/8"	695



GR-750XL WORKING RANGE CHART







NOTE: 1. Boom and jib geometry shown are for unloaded condition and machine standing level on firm supporting surface. Boom deflection and subsequent radius and boom angle change must be accounted for when applying load to hook.






GR-750XL WORKING RANGE CHART



NOTE: 1. Boom and jib geometry shown are for unloaded condition and machine standing level on firm supporting surface.

Boom deflection and subsequent radius and boom angle change must be accounted for when applying load to hook.



GR-750XL RATED LIFTING CAPACITIES (IN POUNDS)

ONOUTRIGGERSFULLYEXTENDED23'11-3/8"(7.3m)SPREAD 360°ROTATION																	
B A	36.1'		49.2'		62.3' (19m)		75.5' (23m)		88.6' (27m)		101.7' (31m)		114.8' (35m)		128.0'	141.1'	
	C	(11m)	C	(15m)	C	C	C	C	C	C	C	C	C	C	(39m)	(43m)	
8'	72	150,000	77	90,000	79	78											
10'	68	132,300	75	90,000	77	70,500	76	44,100									
12'	64	117,100	72	90,000	73	70,500	73	44,100	79	44,100							
15'	59	98,000	68	90,000	69	70,500	69	44,100	77	44,100	79	44,100	79	37,500			
20'	48	75,600	62	75,100	64	69,600	63	44,100	73	44,100	76	42,400	76	37,100			
25'	33	60,000	54	59,400	59	59,100	58	44,100	69	44,100	69	43,300	73	39,100	73	32,600	
30'			46	45,900	52	45,000	52	44,100	65	44,100	65	37,200	70	38,800	69	29,500	
35'			36	33,900	45	32,900	45	38,300	60	34,600	60	32,400	66	34,700	66	25,900	
40'			21	26,100	38	25,300	38	30,200	55	26,800	55	28,500	62	27,700	62	23,100	
45'					29	19,900	28	24,600	50	21,300	50	24,800	58	22,200	58	20,900	
50'					13	15,900	11	20,500	45	17,300	45	20,700	54	18,100	54	19,000	
55'						11,100	14,000	38	14,200	38	17,500	49	15,000	49	17,400	56	15,500
60'								31	11,700	31	15,000	45	12,500	45	15,200	53	13,100
65'								22	9,700	22	13,000	40	10,500	40	13,200	49	11,000
70'												34	8,900	34	11,500	45	9,400
75'												26	7,500	26	10,100	40	8,000
80'												15	6,300	18	9,000	35	6,800
85'																29	5,800
90'																21	5,000
95'																	
100'															31	4,500	
105'															25	3,900	
110'															16	3,300	
115'																	
120'																	
125'																	
130'																	
D																	
Tele mode	0																
	Telescoping conditions (%)																
	I,II	I	I	II	I	II	I	II	I	II	I	II	I	II	I,II		
2nd boom	0	50	100	0	100	0	100	0	100	0	100	0	100	0	50	100	
3rd boom	0	0	0	33	16	50	33	66	50	83	66	100	100	100	100		
4th boom	0	0	0	33	16	50	33	66	50	83	66	100	100	100	100		
Top boom	0	0	0	33	16	50	33	66	50	83	66	100	100	100	100		

LIFTING CAPACITIES AT ZERO DEGREE BOOM ANGLE ON OUTRIGGERS FULLY EXTENDED																												
23' 11-3/8"(7.3m) SPREAD 360° ROTATION																												
C	A	36.1'		49.2'		62.3' (19m)		75.5' (23m)		88.6' (27m)		101.7' (31m)		114.8' (35m)		128.0'		141.1'										
	B	(11m)	B	(15m)	B	B	B	B	B	B	B	B	B	B	B	B	(39m)	B	(43m)									
0	28.0'	26,000	42.0'	16,800	55.4'	10,800	55.4'	13,700	68.6'	7,900	58.6'	10,100	81.7'	6,000	81.7'	8,400	94.2'	4,400	94.5'	6,600	107.9'	3,100	107.0'	4,600	118.6'	2,900	132.5'	1,100
Tele. mode		I,II		I		I		II		I		II		I		II		I		II		I		II		II		I,II

- A** : Boom length in feet
B : Load radius in feet
C : Loaded boom angle ($^{\circ}$)
D : Minimum boom angle ($^{\circ}$) for indicated length (no load)

NOTE: The lifting capacity data stored in the LOAD MOMENT INDICATOR (AML-C) is based on the standard number of parts of line listed in the chart.
Standard number of parts of line for each boom length should be according to the following table.

Boom length in feet (m et ers)	36.1' (11m)	36.1' to 49.2' (11m to 15m)	49.2' to 62.3' (15m to 19m)		62.3' to 141.1' (19m to 43m)	Single top Jib
Telescoping mode	I, II	I		III	I, II	I, II
Number of parts of line	14	8		6 4	4	1

GR-750XL RATED LIFTING CAPACITIES (IN POUNDS)

ON OUTRIGGERSFULLYEXTENDED23'11-3/8"(7.3m) SPREAD													
360° ROTATION													
C	141.1' (43.0m) Boom + 33.2' (10.1m) Jib						C	141.1' (43.0m) Boom + 58.1' (17.7m) Jib					
	3.5°offset		25°offset		45°offset			3.5°offset		25°offset		45°offset	
	R	W	R	W	R	W		R	W	R	W	R	W
80	35.1'	9,300	94.0'	8,800	85.0'	7,500	80	43.0'	5,700	56.0'	5,200	50.0'	4,900
79	38.7'	9,300	95.0'	8,200	86.0'	7,300	79	47.2'	5,700	59.0'	4,900	53.0'	4,700
77	42.0'	9,300	96.0'	7,800	87.0'	7,100	78	51.2'	5,700	57.0'	4,600	49.0'	4,300
76	45.3'	9,100	88.0'	7,200	87.0'	6,900	77	55.1'	5,700	5,600	4,100	86.0'	3,800
75	48.9'	7,800	76.0'	6,400	86.0'	6,700	76	58.7'	5,300	105.09	3,800	186.0'	3,500
73	52.5'	6,700	64.0'	5,800	69.9'	6,600	75	62.7'	4,700	113.82	3,600	191.0'	3,200
70	59.1'	5,800	109.9'	5,200	106.3'	6,300	73	70.2'	4,400	118.88	3,300	199.0'	2,900
68	67.9'	5,100	108.4'	4,600	118.9'	5,900	70	81.4'	3,900	127.98	3,200	132.0'	2,700
65	73.8'	4,100	114.8'	3,800	119.8'	5,700	68	87.9'	3,500	131.9'	3,000	120.0'	2,500
63	83.7'	3,600	119.3'	3,300	119.8'	5,400	65	97.1'	2,800	38.5'	2,800	125.0'	2,100
60	87.3'	2,900	124.7'	2,700	125.7'	5,200	63	103.0'	2,300	42.7'	1,900	141.0'	1,700
58	94.5'	2,500	127.6'	2,300	128.3'	4,900	60	111.9'	1,800	148.6'	1,400	159.0'	1,200
55	99.4'	2,000	132.5'	1,900	133.2'	4,300	58	116.8'	1,400	152.6'	1,200	53.2'	1,000
53	106.3'	1,700	135.8'	1,600		3,500	55	124.3'	1,000				2,400
50	110.6'	1,100	143.7'	1,000		3,100	53	129.3'					1,700
48	116.8'					2,600	50	136.2'					1,300
45	129.7'					2,200	48	140.7'					1,100
43	146.6'					1,800	45	147.3'					
40	130.2'												
38	136.2'												
	139.1'												

ON OUTRIGGERS FULLY EXTENDED 23' 11-3/8"(7.3m) SPREAD													
360° ROTATION													
C	128.0'(39.0m) Boom(telescoping mode I) + 33.2'(10.1m) Jib						C	128.0'(39.0m) Boom(telescoping mode II) + 58.1'(17.7m) Jib					
	3.5° offset		25° offset		45° offset			3.5° offset		25° offset		45° offset	
	R	W	R	W	R	W		R	W	R	W	R	W
80	30.8'	10,100	44.0'	9,500	52.0'	7,700	80	38.7'	6,200	62.0'	5,500	70.0'	4,900
79	34.1'	10,100	46.9'	8,900	55.0'	7,500	79	42.7'	6,200	64.0'	5,300	73.0'	4,700
78	37.4'	10,100	49.5'	8,400	58.0'	7,300	78	45.9'	6,200	66.0'	5,100	76.0'	4,500
76	40.4'	10,100	52.5'	7,700	61.0'	7,200	77	49.9'	6,200	68.0'	4,900	79.0'	4,300
75	43.3'	10,100	55.1'	6,800	63.0'	7,000	76	53.8'	5,500	73.5'	4,800	82.0'	4,100
73	46.6'	10,100	58.1'	6,000	66.0'	6,800	75	56.8'	4,900	76.7'	4,600	85.0'	3,900
70	52.5'	10,000	63.3'	5,400	70.0'	6,500	73	64.3'	4,600	82.5'	4,300	91.0'	3,500
68	60.7'	9,100	70.9'	4,900	77.6'	6,100	70	74.1'	4,100	89.2'	3,900	98.0'	3,100
65	65.9'	8,600	76.1'	4,700	80.7'	5,800	68	80.1'	3,900	91.5'	3,700	103.0'	2,900
63	73.8'	7,900	83.3'	4,300	87.3'	5,500	65	88.6'	3,500	99.3'	3,400	110.0'	2,700
60	78.7'	7,600	87.9'	3,900	91.5'	5,300	63	94.2'	3,400	103.9'	3,300	115.0'	2,500
58	86.3'	6,700	94.5'	3,400	97.8'	5,000	60	102.7'	3,100	110.4'	3,000	122.0'	2,400
55	90.6'	6,200	99.1'	3,100		4,700	58	107.6'	2,800	114.4'	2,900	127.0'	2,300
53	97.1'	5,500	105.3'	2,700	2,400	4,500	55	115.5'	2,400	119.3'	2,800	133.0'	2,100
50	101.4'	5,100	108.9'	2,100		4,500	53	120.4'	2,100	122.6'	2,600	137.0'	1,900
48	107.0'	4,700	114.8'	1,900		4,100	50	127.3'	1,700	128.8'	2,500	143.0'	1,700
45	111.5'	4,300	118.1'	1,700		3,800	48	131.6'	1,500	132.4'	2,400	146.0'	1,500
43	116.8'	3,700	123.0'	1,400		3,300	45	137.5'	1,200	137.7'	2,000	149.0'	1,300
40	120.4'	3,300	126.0'				43	141.4'	1,100	145.0'	1,800		
38	125.0'	2,900	130.2'				40	147.0'			1,500		
35	128.3'	2,600	132.9'				38	150.3'			1,300		
33	132.5'	2,300	136.5'				35	155.2'			1,100		
30	135.5'	2,100	138.8'				33	158.1'			900		
25	139.1'	1,800	142.1'										
20	144.4'	1,500	146.3'										
15	148.6'	1,200											
10	151.6'	1,000											

ON OUTRIGGERS FULLY EXTENDED 23' 11-3/8"(7.3m) SPREAD													
360° ROTATION													
C	114.8'(35m)Boom(telescopingmode I)+33.2'(10.1m)Jib						C	114.8'(35m)Boom(telescopingmode II)+ 58.1'(17.7m)Jib					
	3.5° offset		25° offset		45° offset			3.5° offset		25° offset		45° offset	
	R	W	R	W	R	W		R	W	R	W	R	W
80	28.2'	12,300	40.4'	11,300	47.6'	8,700	80	35.1'	7,100	70.0'	5,600	64.0'	4,200
79	30.8'	12,300	42.7'	10,400	49.5'	8,300	79	38.4'	7,100	73.0'	5,600	74.0'	4,200
78	33.8'	12,300	45.6'	10,400	52.2'	8,300	78	41.7'	7,100	76.0'	5,400	78.0'	4,100
76	36.7'	12,300	48.2'	10,400	54.8'	8,200	77	44.9'	7,100	79.0'	4,700	78.0'	3,800
75	39.7'	12,300	50.5'	10,100	56.8'	8,000	76	48.2'	6,800	81.0'	4,200	78.0'	3,500
73	42.3'	12,300	53.1'	9,900	59.1'	7,800	75	51.2'	5,700	83.0'	3,800	83.4'	3,300
70	47.6'	12,300	58.1'	9,300	63.6'	7,600	73	57.7'	5,200	88.0'	3,400	88.2'	3,100
68	55.1'	11,400	65.0'	8,600	70.2'	7,200	70	67.3'	4,900	93.0'	3,100	93.1'	2,800
65	60.0'	10,800	69.6'	8,200	74.1'	6,900	68	72.8'	4,500	97.0'	2,300	92.8'	2,100
63	67.3'	10,100	76.1'	7,700	80.4'	6,600	65	81.0'	4,300	101.0'	1,700	104.0'	
60	71.9'	9,600	80.4'	7,300	84.3'	6,400	63	86.0'	3,600	105.0'	1,200	108.3'	
55	78.4'	9,000	86.6'	6,900	89.9'	6,200	60	93.5'	2,700	107.0'		114.2'	
53	82.3'	8,300	90.6'	6,700	93.5'	6,000	58	98.4'	2,300	110.4'		117.8'	
50	88.3'	7,000	95.8'	6,200	98.6'	5,800	55	106.6'	1,900	114.7'		123.0'	
48	92.2'	6,300	99.4'	5,600	101.7'	5,300	53	110.2'	1,700	117.8'		126.3'	
45	97.4'	5,300	104.7'	4,800	106.3'	4,600	50	116.5'	1,400	120.6'		130.5'	
43	101.0'	4,600	107.6'	4,300	108.9'	4,200	48	120.4'	1,200	122.9'		133.5'	
40	106.0'	4,100	112.2'	3,700	113.2'	3,600	45	126.3'	1,000			137.5'	
38	109.3'	3,700	114.8'	3,400			43	129.9'					
35	113.8'	3,200	119.1'	3,000			40	135.2'					
33	116.8'	2,900	121.4'	2,700			38	138.5'					
25	121.1'	2,500	125.0'	2,300			35	142.7'					
20	123.4'	2,300	127.0'	2,100			33	145.7'					
15	127.0'	2,000	129.9'	1,900			30	149.6'					
	132.2'	1,600	133.9'	1,500									
	136.2'	1,300											
	139.1'	1,100											

C :Loaded boom angle (°)
R :Load radius in feet
W :Rated lifting capacity in pounds



GR-750XL RATED LIFTING CAPACITIES (IN POUNDS)

ON OUTRIGGERS MID EXTENDED 21' 11-3/4" (6.7m) SPREAD

Web: www.brigge.com

360° ROTATION

A		36.1'		49.2'		62.3' (19m)		75.5' (23m)		88.6' (27m)		101.7' (31m)		114.8' (35m)		128.0'		141.1'							
B	C	(11m)		C (15m)		C		C		C		C		C		C		C (39m)		C (43m)					
8'	72	150,000		77	90,000		79	78																	
10'	68	130,000	75	90,000	77	70,500	76	44,100																	
12'	64	113,600	72	90,000	73	70,500	73	44,100	79	44,100	79	44,100													
15'	58	94,800	68	90,000	69	70,500	69	44,100	77	44,100	77	44,100	79	44,100	79	37,500									
20'	48	72,700	62	72,200	64	69,600	63	44,100	73	44,100	73	44,100	76	42,400	76	37,100	78	36,600	78	31,700					
25'	33	54,300	55	52,700	58	51,700	58	44,100	69	44,100	69	43,300	73	39,100	73	32,600	76	32,400	76	28,100					
30'																									
35'				47	36,200	52	35,300	52	40,900	65	37,100	65	37,200	70	38,100	69	29,500	73	30,600	73	25,200				
40'				36	26,500	45	25,700	45	30,800	60	27,300	60	31,300	66	28,200	66	25,900	70	28,900	70	23,500				
45'				22	20,100	38	19,500	37	24,300	55	20,900	55	24,800	62	21,800	62	23,100	67	22,500	66	20,900				
50'						28	15,000	27	19,600	50	16,400	50	20,100	58	17,300	58	20,400	63	17,900	63	18,800				
55'						11	11,700	10	16,100	45	13,100	45	16,600	54	13,900	54	16,900	60	14,500	60	17,100				
60'							9,100		13,400	38	10,500	38	14,000	49	11,400	49	14,300	56	11,900	56	14,400				
65'										31	8,400	31	11,800	45	9,300	45	12,100	52	9,800	53	12,300				
70'										21	6,700	21	10,100	39	7,600	39	10,400	49	8,100	49	10,600				
75'														34	6,200	34	8,900	45	6,700	45	9,100				
80'														26	5,000	26	7,700	40	5,600	40	7,900				
85'														15	4,000	15	6,700	35	4,500	35	6,900				
90'																		29	3,700	29	6,000				
95'														21	2,900	21	5,200	36	4,100	36	5,200				
100'																			31	2,600	30	4,600			
105'																			24	2,000	24	4,000			
110'																			15	1,500	15	3,500			
115'																									
120'																			27	2,200	28	1,500			
D																			8	1,500					
Tele. mode										0											33				
										Telescoping conditions (%)															
			I, II		I		I		II		I		II		I		II		I		II				
2nd boom	0		50		100		0		100		0		100		0		100		0		50				
3rd boom	0		0		0		33		16		50		33		66		50		83		66				
4th boom	0		0		0		33		16		50		33		66		50		83		66				
Top boom	0		0		0		33		16		50		33		66		50		83		66				
LIFTING CAPACITIES AT ZERO DEGREE BOOM ANGLE ON OUTRIGGERS MID EXTENDED																									
21' 11-3/4" (6.7m) SPREAD 360° ROTATION																									

NOTE: The lifting capacity data stored in the LOAD MOMENT INDICATOR (AML-C) is based on the standard number of parts of line listed in the chart.
Standard number of parts of line for each boom length should be according to the following table.

Boom length in feet (m et ers)	36.1' (11m)	36.1' to 49.2' (11m to 15m)	49.2' to 62.3' (15m to 19m)	62.3' to 141.1' (19m to 43m)	Single top Jib
Telescoping mode	I, II	I	III	I, II	I, II
Number of parts of line	14	8	6 4	4	1

GR-750XL RATED LIFTING CAPACITIES (IN POUNDS)

ON OUTRIGGERS MIDEXTENDED 21'11-3/4"(6.7m)SPREAD													
360° ROTATION													
C	141.1' (43.0m) Boom + 33.2' (10.1m) Jib							141.1' (43.0m) Boom + 58.1' (17.7m) Jib					
	3.5° offset		25° offset		45° offset			3.5° offset		25° offset		45° offset	
	R	W	R	W	R	W		R	W	R	W	R	W
80	35.1'	9,300	48.6'	8,800	55.4'	7,500	80	43.0'	5,700	65.6'	5,200	76.8'	3,900
79	38.7'	9,300	51.8'	8,500	58.4'	7,300	79	47.2'	5,700	69.2'	5,000	80.1'	3,800
77	42.0'	9,300	54.8'	8,200	61.0'	7,100	78	51.2'	5,700	72.5'	4,900	83.3'	3,700
76	45.3'	9,300	58.1'	8,000	64.3'	6,900	77	55.1'	5,700	75.8'	4,700	86.0'	3,700
75	48.9'	9,300	61.0'	7,800	66.9'	6,700	76	58.7'	5,700	79.1'	4,600	89.2'	3,600
73	52.5'	9,300	64.0'	7,500	69.9'	6,600	75	62.7'	5,700	82.3'	4,400	92.2'	3,500
70	59.1'	9,100	69.9'	7,200	75.1'	6,300	73	70.2'	5,700	88.9'	4,100	97.8'	3,400
68	67.9'	8,200	78.4'	6,700	83.3'	5,900	70	81.4'	5,600	98.8'	3,800	106.0'	3,200
65	73.8'	7,800	84.0'	6,400	87.6'	5,700	68	87.9'	5,300	105.0'	3,600	111.2'	3,000
63	81.4'	6,100	90.9'	5,200	94.6'	4,800	65	96.1'	4,100	112.6'	3,200	118.4'	2,800
60	86.0'	5,200	95.5'	4,500	98.8'	4,100	63	101.4'	3,400	117.8'	2,600	123.0'	2,300
58	93.2'	4,000	102.0'	3,500	105.0'	3,200	60	109.3'	2,500	125.0'	1,900	129.3'	1,700
56	97.8'	3,300	106.3'	2,900	108.9'	2,700	58	113.2'	2,000	129.3'	1,500	133.5'	1,300
53	104.7'	2,500	112.5'	2,200	114.8'	2,000	55	122.0'	1,300	136.2'	1,000	139.4'	900
50	108.9'	2,000	116.8'	1,800	118.4'	1,600	53	126.6'					
48	115.2'	1,400	122.7'	1,200	123.7'	1,100			900				
	119.4'	1,100	126.3'	900	127.3'	900							

ON OUTRIGGERS MID EXTENDED 21' 11-3/4"(6.7m) SPREAD													
360° ROTATION													
C	128.0'(39.0m) Boom(telescoping mode II) + 33.2' (10.1m) Jib						C	128.0'(39.0m) Boom(telescoping mode II) + 58.1' (17.7m) Jib					
	3.5° offset		25° offset		45° offset			3.5° offset		25° offset		45° offset	
	R	W	R	W	R	W		R	W	R	W	R	W
79	30.8'	10,100	44.0'	9,500	51.5'	7,700	80	38.7'	6,200	60.7'	5,500	72.5'	4,100
78	34.1'	10,100	46.9'	9,200	54.1'	7,500	79	42.7'	6,200	64.0'	5,300	75.1'	3,900
77	37.4'	10,100	49.5'	8,900	56.8'	7,300	78	45.9'	6,200	67.3'	5,100	78.1'	3,900
76	40.4'	10,100	52.5'	8,600	59.4'	7,200	77	49.9'	6,200	70.2'	4,900	80.7'	3,800
75	43.3'	10,100	55.1'	8,400	61.7'	7,000	76	53.5'	6,200	73.5'	4,800	83.3'	3,700
73	46.6'	10,100	58.1'	8,200	64.0'	6,800	75	56.8'	6,200	76.1'	4,600	86.0'	3,600
70	52.5'	10,000	63.3'	7,700	68.9'	6,500	73	64.3'	6,200	82.3'	4,300	91.2'	3,400
68	60.7'	9,100	70.9'	7,100	76.4'	6,100	70	74.1'	6,000	91.2'	3,900	98.8'	3,200
65	65.9'	8,600	76.1'	6,800	80.7'	5,800	68	80.1'	5,500	96.5'	3,700	103.7'	3,100
63	73.8'	7,900	83.3'	6,300	87.3'	5,500	65	88.6'	4,900	104.7'	3,400	110.6'	2,900
60	79.1'	7,400	87.9'	6,000	91.5'	5,300	63	94.2'	4,600	109.6'	3,300	115.8'	2,800
58	85.6'	6,000	94.5'	5,200	97.8'	4,900	60	102.7'	4,100	117.1'	3,000	122.7'	2,700
55	89.9'	5,200	98.4'	4,600	101.4'	4,300	58	107.3'	3,500	122.4'	2,800	127.3'	2,500
53	96.5'	4,300	104.3'	3,800	107.0'	3,600	55	114.2'	2,800	128.6'	2,200	132.9'	2,000
50	100.4'	3,700	107.9'	3,300	110.6'	3,200	53	119.1'	2,300	132.5'	1,900	136.2'	1,700
48	106.3'	3,000	113.5'	2,700	115.5'	2,600	50	125.7'	1,800	138.5'	1,400	141.1'	1,300
45	110.2'	2,600	116.8'	2,400	118.4'	2,300	48	129.9'	1,500	142.1'	1,200	143.7'	1,100
43	115.5'	2,100	121.7'	1,900	123.0'	1,800	45	136.2'	1,000	147.3'			
40	119.1'	1,800	125.0'	1,700			43	140.1'			900		
38	124.3'	1,400	129.6'	1,300					900				
35	127.3'	1,200	132.2'	1,100									
	131.9'	900	136.2'	900									

ON OUTRIGGERS MID EXTENDED 21' 11-3/4" (6.7m) SPREAD													
360° ROTATION													
C	114.8'(35m) Boom(telescoping mode I) + 33.2' (10.1m) Jib						C	114.8'(35m) Boom(telescoping mode I) + 58.1' (17.7m) Jib					
	3.5° offset		25° offset		45° offset			3.5° offset		25° offset		45° offset	
	R	W	R	W	R	W		R	W	R	W	R	W
79	28.2'	12,300	40.4'	11,300	47.6'	8,700	80	35.1'	7,100	56.8'	6,200	68.9'	4,500
78	30.8'	12,300	42.7'	10,400	49.5'	8,300	79	38.4'	7,100	59.4'	5,600	71.2'	4,200
77	33.8'	12,300	45.6'	10,400	52.2'	8,300	78	41.7'	7,100	62.7'	5,600	73.8'	4,200
76	36.7'	12,300	48.2'	10,400	54.8'	8,200	77	44.9'	7,100	65.6'	5,600	76.8'	4,200
75	39.7'	12,300	50.5'	10,100	56.8'	8,000	76	48.2'	7,100	68.6'	5,500	79.1'	4,200
73	42.3'	12,300	53.1'	9,900	59.1'	7,800	75	51.2'	7,100	71.2'	5,400	81.7'	4,100
70	47.6'	12,300	58.1'	9,300	63.6'	7,600	73	57.7'	7,100	76.8'	5,000	86.3'	4,000
68	55.1'	11,400	65.0'	8,600	70.2'	7,200	70	67.3'	7,100	84.6'	4,700	93.2'	3,800
65	60.0'	10,800	69.6'	8,200	74.1'	6,900	68	72.8'	6,800	89.9'	4,500	97.6'	3,600
63	66.0'	9,800	76.1'	7,700	80.4'	6,600	65	81.0'	6,100	97.8'	4,200	104.0'	3,500
60	71.2'	8,500	80.4'	7,100	84.3'	6,400	63	86.0'	5,700	102.0'	4,000	108.3'	3,400
58	77.4'	6,800	86.0'	5,900	89.6'	5,400	60	93.2'	4,700	108.9'	3,700	114.2'	3,300
55	81.4'	6,000	89.6'	5,200	92.8'	4,800	58	97.8'	4,000	112.9'	3,200	117.5'	2,800
53	87.3'	4,900	95.1'	4,200	98.1'	4,000	55	104.3'	3,200	119.1'	2,500	122.7'	2,300
50	90.9'	4,200	98.8'	3,700	101.0'	3,500	53	108.6'	2,700	122.7'	2,200	126.0'	1,900
48	96.5'	3,400	103.7'	3,000	105.6'	2,900	50	114.8'	2,100	128.3'	1,700	130.2'	1,500
45	100.1'	3,000	107.0'	2,600	108.3'	2,500	48	119.1'	1,700	131.6'	1,400	133.5'	1,200
43	105.3'	2,400	111.5'	2,100	112.5'	2,000	45	125.0'	1,200	136.5'	1,000	137.5'	900
40	108.6'	2,000	114.2'	1,800			43	128.6'					
38	113.2'	1,600	118.4'	1,400					900				
35	116.1'	1,300	121.1'	1,200									
	120.4'	1,000	124.3'	1,000									

C : Loaded boom angle (°)

R : Load radius in feet

W : Rated lifting capacity in pounds

GR-750XL RATED LIFTING CAPACITIES (IN POUNDS)

ONOUTRIGGERSMIDEXTENDED18'1/2"(5.5m)SPREAD 360 ROTATION																			
B A	36.1'		49.2'		62.3' (19m)		75.5' (23m)		88.6' (27m)		101.7' (31m)		114.8' (35m)		128.0'		141.1'		
	C	(11m)	C	(15m)	C	C	C	C	C	C	C	C	C	C	C	(39m)	C	(43m)	
8'	72	150,000	77	90,000	79		78												
10'	68	121,200	75	90,000	77	70,500	76	44,100											
12'	64	105,100	72	90,000	73	70,500	73	44,100	79	44,100	79	44,100							
15'	58	87,000	68	86,500	69	70,500	69	44,100	77	44,100	77	44,100	79	44,100	79	37,500			
20'	48	61,000	62	60,000	64	59,200	63	44,100	73	44,100	76	42,400	76	37,100	78	36,600	78	31,700	
25'	33	38,700	54	37,800	58	37,300	58	42,900	69	39,100	69	43,300	73	39,100	73	32,400	76	32,400	
30'				46	26,200	52	25,700	52	30,800	65	27,500	65	31,500	69	28,500	69	29,500	73	29,200
35'				35	19,000	45	18,500	45	23,300	60	20,200	60	24,000	66	21,200	66	24,400	70	21,900
40'				21	14,200	38	13,700	38	18,200	55	15,300	55	18,900	62	16,300	62	19,300	66	17,000
45'						29	10,200	28	14,600	50	11,700	50	15,200	58	12,700	58	15,600	63	13,300
50'						12	7,600	11	11,800	45	9,100	45	12,400	54	10,000	54	12,800	60	10,600
55'							5,600		9,700	38	7,000	38	10,300	49	7,800	49	10,600	56	8,500
60'										31	5,300	31	8,600	45	6,200	44	8,900	52	6,800
65'										22	3,900	21	7,200	39	4,800	39	7,500	48	5,400
70'													34	3,600	34	6,300	45	4,200	
75'													26	2,700	25	5,300	39	3,200	
80'													15	1,900	15	4,500	34	2,400	
85'																	28	1,700	
90'															21	3,300	36	1,500	
95'																	30	2,900	
100'																	24	2,400	
105'																	15	2,000	
D																			
Tele. mode	0											21	0	24	0	32	45		
Telescoping conditions (%)																			
	I,II		I		I		II		I		II		I		II		I		
2nd boom	0		50		100		0		100		0		100		0		100		
3rd boom	0		0		0		33		16		50		33		66		50		
4th boom	0		0		0		33		16		50		33		66		50		
Top boom	0		0		0		33		16		50		33		66		50		

LIFTING CAPACITIES AT ZERO DEGREE BOOM ANGLE ON OUTRIGGERS MID EXTENDED 18'1/2" (5.5m) SPREAD 360° ROTATION														
C	A	36.1' (11m)		49.2' (15m)		62.3' (19m)		75.5' (23m)		88.6' (27m)		101.7' (31m)		114.8' (35m)
	B	B	B	B	B	B	B	B	B	B	B	B	B	B
0	28.9°	25,800	42.3°	12,600	55.4°	5,500	55.4°	9,700	71.9°	3,100	58.6°	6,400	81.7°	4,200
Tele. mode		I,II	I	I	II	I	II	I	II	I	II	I	II	II

- A** : Boom length in feet
B : Load radius in feet
C : Loaded boom angle (°)
D : Minimum boom angle (°) for indicated length (no load)

NOTE: The lifting capacity data stored in the LOAD MOMENT INDICATOR (AML-C) is based on the standard number of parts of line listed in the chart.
 Standard number of parts of line for each boom length should be according to the following table.

Boom length in feet (m et ers)	36.1' (11m)	36.1' to 49.2' (11m to 15m)	49.2' to 62.3' (15m to 19m)	62.3' to 141.1' (19m to 43m)	Single top Jib
Telescoping mode	I, II	I		III	I, II
Number of parts of line	14	8		6 4	1

GR-750XL RATED LIFTING CAPACITIES (IN POUNDS)

ON OUTRIGGERS MIDEXTENDED18'1/2"(5.5m)SPREAD													
360°ROTATION													
C80	141.1' (43.0m) Boom + 33.2' (10.1m) Jib						C	141.1' (43.0m) Boom + 58.1' (17.7m) Jib					
	3.5° offset		25° offset		45° offset			3.5° offset		25° offset		45° offset	
	R	W	R	W	R	W		R	W	R	W	R	W
79	35.1'	9,300	48.6'	8,800	55.4'	7,500	80	43.0'	5,700	65.6'	5,200	76.8'	3,900
78	38.7'	9,300	51.8'	8,500	58.4'	7,300	79	47.2'	5,700	69.2'	5,000	80.1'	3,800
77	42.0'	9,300	54.8'	8,200	61.0'	7,100	78	51.2'	5,700	72.5'	4,900	83.3'	3,700
76	45.3'	9,300	58.1'	8,000	64.3'	6,900	77	55.1'	5,700	75.8'	4,700	86.0'	3,700
75	48.9'	9,300	61.0'	7,800	66.9'	6,700	76	58.7'	5,700	79.1'	4,600	89.2'	3,600
73	52.5'	9,300	64.0'	7,500	69.9'	6,600	75	62.7'	5,700	82.3'	4,400	92.2'	3,500
70	56.4'	8,300	68.0'	6,900	74.8'	6,200	73	69.9'	5,400	88.9'	4,100	97.8'	3,400
68	66.3'	6,200	76.8'	5,300	81.7'	4,800	70	78.7'	3,900	96.8'	3,000	105.3'	2,700
65	71.5'	5,100	81.7'	4,400	86.3'	4,100	68	84.3'	3,100	102.0'	2,400	109.6'	2,200
63	79.1'	3,800	90.9'	3,300	92.8'	3,000	65	92.5'	2,100	109.6'	1,600	116.6'	1,500
60	84.0'	3,000	93.5'	2,700	97.1'	2,400	63	98.1'	1,500	114.8'	1,100	121.4'	1,100
58	91.5'	2,100	100.4'	1,900	103.7'	1,700	60	107.0'	1,100				
55	96.1'	1,600	105.0'	1,400	107.6'	1,300							
	103.0'												
		900											

ON OUTRIGGERS MID EXTENDED 18' 1/2"(5.5m) SPREAD													
360° ROTATION													
C80	128.0'(39.0m) Boom(telescoping mode II) + 33.2' (10.1m) Jib						C	128.0'(39.0m) Boom(telescoping mode II) + 58.1' (17.7m) Jib					
	3.5° offset		25° offset		45° offset			3.5° offset		25° offset		45° offset	
	R	W	R	W	R	W		R	W	R	W	R	W
79	30.8'	10,100	44.0'	9,500	51.5'	7,700	80	38.7'	6,200	60.7'	5,500	72.5'	4,100
78	34.1'	10,100	46.9'	9,200	54.1'	7,500	79	42.7'	6,200	64.0'	5,300	75.1'	3,900
77	37.4'	10,100	49.5'	8,900	56.8'	7,300	78	45.9'	6,200	67.3'	5,100	78.1'	3,900
76	40.4'	10,100	52.5'	8,600	59.4'	7,200	77	49.9'	6,200	70.2'	4,900	80.7'	3,800
75	43.3'	10,100	55.1'	8,400	61.7'	7,000	76	53.5'	6,200	73.5'	4,800	83.3'	3,700
73	46.6'	10,100	58.1'	8,200	64.0'	6,800	75	56.8'	6,200	76.1'	4,600	86.0'	3,600
70	52.5'	10,000	63.3'	7,700	68.9'	6,500	73	64.3'	6,200	82.3'	4,300	91.2'	3,400
68	60.7'	9,100	70.9'	7,100	76.4'	6,100	70	74.1'	6,000	91.2'	3,900	98.6'	3,200
65	66.6'	7,700	76.8'	6,400	80.7'	5,800	68	79.4'	5,100	96.5'	3,700	103.7'	3,100
63	72.6'	6,000	82.3'	5,100	86.6'	4,700	65	87.6'	3,900	104.0'	3,100	110.2'	2,700
60	77.1'	5,100	86.6'	4,400	90.6'	4,000	63	92.5'	3,300	108.6'	2,600	114.8'	2,200
58	84.0'	4,000	92.8'	3,400	96.5'	3,200	60	100.1'	2,400	115.2'	1,900	121.1'	1,700
55	88.3'	3,300	96.8'	2,900	100.4'	2,700	58	105.0'	2,000	119.8'	1,500	125.0'	1,300
53	94.8'	2,500	102.7'	2,200	106.0'	2,100	55	112.2'	1,300	126.3'	1,000		
50	98.8'	2,100	106.6'	1,800	109.3'	1,700	53	117.1'	1,000				
48	105.0'	1,500	112.2'	1,300	114.2'	1,200							
	108.9'	1,200	115.8'	1,000	117.5'	900							

ON OUTRIGGERS MID EXTENDED 18' 1/2"(5.5m) SPREAD													
360° ROTATION													
C 80	114.8'(35m) Boom(telescoping mode I) + 33.2' (10.1m) Jib						C	114.8'(35m) Boom(telescoping mode I) + 58.1' (17.7m) Jib					
	3.5° offset		25° offset		45° offset			3.5° offset		25° offset		45° offset	
	R	W	R	W	R	W		R	W	R	W	R	W
79	28.2'	12,300	40.4'	11,300	47.6'	8,700	80	35.1'	7,100	56.8'	6,200	68.9'	4,500
78	30.8'	12,300	42.7'	10,400	49.5'	8,300	79	38.4'	7,100	59.4'	5,600	71.2'	4,200
77	33.8'	12,300	45.6'	10,400	52.2'	8,300	78	41.7'	7,100	62.7'	5,600	73.8'	4,200
76	36.7'	12,300	48.2'	10,400	54.8'	8,200	77	44.9'	7,100	65.6'	5,600	76.8'	4,200
75	39.7'	12,300	50.5'	10,100	56.8'	8,000	76	48.2'	7,100	68.6'	5,500	79.1'	4,200
73	42.3'	12,300	53.1'	9,900	59.1'	7,800	75	51.2'	7,100	71.2'	5,400	81.7'	4,100
70	47.6'	12,300	58.1'	9,300	63.6'	7,600	73	57.7'	7,100	76.8'	5,000	86.3'	4,000
68	55.4'	10,700	65.0'	8,500	70.2'	7,200	70	67.3'	7,100	84.6'	4,700	93.2'	3,800
65	59.4'	9,000	69.2'	7,300	74.1'	6,500	68	72.2'	6,000	89.9'	4,500	97.8'	3,600
63	65.9'	6,900	75.1'	5,800	79.4'	5,200	65	79.4'	4,700	96.5'	3,500	103.3'	3,000
60	69.9'	5,900	79.1'	4,900	83.3'	4,600	63	84.3'	3,900	100.7'	2,900	107.3'	2,500
58	76.4'	4,500	85.0'	3,900	88.6'	3,500	60	91.2'	2,900	107.3'	2,200	113.2'	1,900
55	80.4'	3,800	88.6'	3,300	92.2'	3,000	58	96.1'	2,300	111.5'	1,800	116.8'	1,500
53	86.3'	2,900	94.2'	2,500	97.1'	2,300	55	103.0'	1,600	117.5'	1,200	122.0'	1,000
50	89.9'	2,400	97.8'	2,100	100.4'	1,900	53	107.3'	1,200				
48	95.5'	1,700	102.7'	1,500	105.0'	1,400							
	99.1'	1,300	106.0'	1,100	107.9'	1,100							

C : Loaded boom angle (°)

R : Load radius in feet

W : Rated lifting capacity in pounds

GR-750XL RATED LIFTING CAPACITIES (IN POUNDS)

ONOUTRIGGERSMINEXTENDED8'10-5/16"(2.7m)SPREAD 360 ROTATION																					
B A	36.1'		49.2'		62.3' (19m)			75.5' (23m)			88.6' (27m)			101.7' (31m)			114.8' (35m)			128.0'	141.1'
	C	(11m)	C	(15m)	C	C	C	C	C	C	C	C	C	C	C	C	C	(39m)	C	(43m)	
8'	72	128,500	77	90,000	79		78														
10'	68	79,000	74	77,300	76	70,500	76	44,100													
12'	64	55,700	72	54,200	73	53,200	73	44,100	79	44,100	79	44,100									
15'	58	37,100	68	36,000	69	35,200	68	40,700	77	36,900	77	41,300	79	38,000	79	37,500					
20'	47	21,800	61	21,100	63	20,400	63	25,200	73	21,900	73	25,700	76	22,800	76	26,100	78	23,500	78	26,300	
25'	32	14,000	54	13,300	58	12,900	58	17,300	69	14,200	69	17,800	72	15,100	72	18,100	76	15,700	75	18,300	
30'			46	8,600	51	8,100	51	12,300	64	9,600	64	12,900	69	10,400	69	13,200	72	10,900	72	13,400	
35'			35	5,400	45	4,900	45	9,000	59	6,300	59	9,800	69	5,700	69	8,200	72	6,000	72	8,100	
40'			21	3,100		2,600	37	6,600	55	4,000	55	2,200	56	4,900	61	66	5,400	66	7,800		
45'							28	4,800	50	2,200	50	5,400	58	3,100	57	63	3,700	62	6,000		
50'							11	3,400			44	3,900	53	1,700	53	59	2,300	59	4,600		
55'								2,300			38	2,800		49			55	3,400	60	1,600	
60'											31	1,900		44			52	2,500		57	
65'														38			48	1,700		54	
D	0				38	0		45		21		52		33		58		44		58	
Tele. mode																					
	I,II		I		I		II		I		II		I		II		I		II		
2nd boom	0		50		100		0		100		0		100		0		100		0		
3rd boom	0		0		0		33		16		50		33		66		50		83		
4th boom	0		0		0		33		16		50		33		66		50		83		
Top boom	0		0		0		33		16		50		33		66		50		83		

LIFTING CAPACITIES AT ZERO DEGREE BOOM ANGLE ON OUTRIGGERS MIN EXTENDED 8' 10-5/16" (2.7m) SPREAD 360° ROTATION															
C \ A	36.1' (11m)		49.2' (15m)		62.3' (19m)										
	B		B		B										
0	28.9	9,900	42.0	2,000	55.4	2,200									
Tele. mode	I, II		I		II										

- A** : Boom length in feet
B : Load radius in feet
C : Loaded boom angle (°)
D : Minimum boom angle (°) for indicated length (no load)

NOTE: The lifting capacity data stored in the LOAD MOMENT INDICATOR (AML-C) is based on the standard number of parts of line listed in the chart.
 Standard number of parts of line for each boom length should be according to the following table.

Boom length in feet (m et ers)	36.1' (11m)	36.1' to 49.2' (11m to 15m)	49.2' to 62.3' (15m to 19m)	62.3' to 141.1' (19m to 43m)	Single top Jib
Telescoping mode	I, II	I		III	I, II
Number of parts of line	14	8		6 4	4

WARNING AND OPERATING INSTRUCTIONS FOR LIFTING CAPACITIES

GENERAL

1. RATED LIFTING CAPACITIES apply only to the machine as originally manufactured and normally equipped by TADANO LTD. Modifications to the machine or use of optional equipment other than that specified can result in a reduction of capacity.
2. Hydraulic cranes can be hazardous if improperly operated or maintained. Operation and maintenance of this machine must be in compliance with information in the **Operation and Maintenance Manual** supplied with the crane. If this manual is missing, order a replacement through the distributor.
3. The operator and other personnel associated with this machine shall fully acquaint themselves with the latest applicable ASME B30.5 safety standards for cranes as mentioned in OSHA CFR29 part 1926.

SET UP

1. Rated lifting capacities on the load chart are the maximum allowable crane capacities. They are based on the machine standing level on firm supporting surface under ideal job conditions. Depending on the nature of the supporting surface, it may be necessary to have structural supports under the outrigger floats or tires to spread the loads to a larger surface.
2. For outrigger operation, outriggers shall be properly extended with tires free of supporting surface before operating crane.

OPERATION

1. Rated lifting capacities have been tested to and meet minimum requirements of SAE J1063-Cantilevered Boom Crane Structures Method of Test.
2. Rated lifting capacities do not exceed 85 % of the tipping load on outriggers fully extended as determined by SAE J765-Crane Stability Test Code.
Rated lifting capacities for partially extended outriggers are determined from the formula, Rated Lifting Capacities = (Tipping Load - 0.1 x Tip Reaction) / 1.25.
3. Rated lifting capacities above bold lines in the chart are based on crane strength and those below, on its stability. They are based on actual load radius increased by boom deflection.
4. The weight of handling device such as hook blocks, slings, etc., must be considered as part of the load and must be deducted from the lifting capacities.
5. Rated lifting capacities are based on freely suspended loads and make no allowance for such factors as the effect of wind, sudden stopping of loads, supporting surface conditions, inflation of tires, operating speeds, side loads, etc. Side pull on the boom or jib is extremely dangerous. Such action can damage the boom, jib or swing mechanism, and lead to overturning the crane.
6. Rated lifting capacities do not account for wind on lifted load or boom. We recommend against working under the condition that the load is out of control due to a strong wind. During boom lift, consider that the rated lifting capacity is reduced by 50% when the wind speed is 20mph(9m/s) to 27mph(12m/s); reduced by 70% when the wind speed is 27mph(12m/s) to 31mph(14m/s). If the wind speed is 31mph(14m/s) or over, stop operation. During jib lift, stop operation if the wind speed is 20mph(9m/s).
7. Rated lifting capacities at load radius shall not be exceeded. Do not tip the crane to determine allowable loads.
8. Do not operate at boom lengths, radii, or boom angle, where no capacities are shown. Crane may overturn without any load on the hook.
9. When boom length is between values listed, refer to the rated lifting capacities of the next longer and next shorter booms for the same radius. The lesser of the two rated lifting capacities shall be used.
10. When making lifts at a load radius not shown, use the next longer radius to determine allowable capacity.
11. Load per line should not exceed 12,300 lbs. (5,600kg) for main hoist and auxiliary hoist.
12. Check the actual number of parts of line with LOAD MOMENT INDICATOR (AML-C) before operation. Maximum lifting capacity is restricted by the number of parts of line of LOAD MOMENT INDICATOR (AML-C). Limited capacity is as determined from the formula, Single line pull for main hoist 12,300 lbs. (5,600kg) x number of parts of line.
13. The boom angle before loading should be greater to account for deflection. For rated lifting capacities, the loaded boom angle and the load radius is for reference only.
14. The 36.1' (11.0m) boom length capacities are based on boom fully retracted. If not fully retracted [less than 49' (15.0m) boom length], use the rated lifting capacities for the 49' (15.0m) boom length.
15. Extension or retraction of the boom with loads may be attempted within the limits of the RATED LIFTING CAPACITIES. The ability to telescope loads is limited by hydraulic pressure, boom angle, boom length, crane maintenance, etc.
16. For lifting capacity of single top, reduce the rated lifting capacities of relevant boom according to a weight reductions for auxiliary load handling equipment. Capacities of single top shall not exceed 12,300 lbs. (5,600kg) including main hook.
17. When base jib or top jib or both jib removing, jib state switch select removed.
18. When erecting and stowing jib, be sure to retain it by hand or by other means to prevent its free movement.
19. Use "ANTI-TWO BLOCK" disable switch when erecting and stowing jib and when stowing hook block. While the switch is pushed, the hoist does not stop, even when overwind condition occurs.
20. For boom length 141.1' (43.0m) or less and 114.8' (35.0m) or longer with jib, rated lifting capacities are determined by loaded boom angle only in the column headed "141.1' (43.0m)boom+jib". For boom length 114.8' (35.0m) or less with jib, rated lifting capacities are determined by loaded boom angle only in the column headed "114.8' (35.0m)boom+jib". For angles not shown, use the next lower loaded boom angle to determine allowable capacity. (Telescoping MODE I)
For boom length 141.1' (43.0m) or less and 128.0' (39.0m) or longer with jib, rated lifting capacities are determined by loaded boom angle only in the column headed "141.1' (43.0m)boom+jib". For boom length 128.0' (39.0m) or less with jib, rated lifting capacities are determined by loaded boom angle only in the column headed "128.0'(39.0m)boom+jib". For angles not shown, use the next lower loaded boom angle to determine allowable capacity. (Telescoping MODE II)
21. When lifting a load by using jib (aux. hoist) and boom (main hoist) simultaneously, do the following:
Enter the operation status as jib operation, not as boom operation.
Before starting operation, make sure that mass of load is within rated lifting capacity for jib.
22. Before telescoping the boom, set the telescoping mode selector switch to MODE I or MODE II with the boom fully retracted. A change of the telescoping mode is not permissible when the boom has been partially or fully extended.
23. Crane operation is prohibited without full counterweight 12,500lbs. (5.7 ton) installed. Outriggers shall be extended 23' 11 3/8" (7.3m) spread when installing or removing counterweight.

DEFINITIONS

1. Load Radius: Horizontal distance from a projection of the axis of rotation to supporting surface before loading to the center of the vertical hoist line or tackle with load applied.
2. Loaded Boom Angle: The angle between the boom base section and the horizontal, after lifting the rated lifting capacity at the load radius.
3. Working Area: Area measured in a circular arc about the centerline of rotation.
4. Freely Suspended Load: Load hanging free with no direct external force applied except by the hoist line.
5. Side Load: Horizontal side force applied to the lifted load either on the ground or in the air.

GR-750XL RATED LIFTING CAPACITIES (IN POUNDS)


ON RUBBER																		
A B	Stationary											Creep						
	Over Front						360° Rotation					Over Front						
	36.1'		62.3'		88.6'		36.1'		62.3'		88.6'		36.1'		62.3'		88.6'	
C	(11m)	C	(19m)	C	(27m)	C	(11m)	C	(19m)	C	(27m)	C	(11m)	C	(19m)	C	(27m)	
10'	68	65,000					68	41,000				68	51,000					
12'	64	60,000					64	29,000				64	44,000					
15'	59	50,000	73	35,000			58	20,000	73	22,000			58	36,000	73	35,000		
20'	48	34,000	69	35,000			47	12,000	68	14,000	72	10,000	48	27,000	68	28,000		
25'	32	23,000	63	25,000	73	22,000	33	7,500	63	9,500	69	7,000	32	21,000	63	22,000	73	22,000
30'			58	18,000	69	19,000			58	6,500	65	5,000			58	17,000	69	18,000
35'			51	14,000	65	15,000			51	4,500	61	3,500			52	13,000	65	14,000
40'			45	11,000	62	12,000			46	3,000	57	2,300			45	10,000	61	11,000
45'			38	8,000	58	9,500									37	7,500	57	9,000
50'			28	6,000	54	7,500									28	5,500	53	7,000
55'			11	4,500	49	6,000									11	4,000	49	5,500
60'					44	5,000											44	4,500
65'					39	4,000											39	3,500
70'					33	3,000											33	2,500
D	0					0			37			54		0				
Tele. mode	Telescoping conditions (%)																	
2nd boom	I,II		II		II		I, II		II		II		I, II		33		II	
3rd boom	0		0		0		0		0		0		0		33		0	
4th boom	0		33		66		0		33		66		0		33		66	
Top boom	0		33		66		0		33		66		0		33		66	
	0		33		66		0		33		66		0		33		66	

LIFTING CAPACITIES AT ZERO DEGREE BOOM ANGLE ON RUBBER OPERATION																
A	Stationary										Creep					
	Over Front					360°Rotation					Over Front					
	36.1'	62.3'	88.6'	36.1'	62.3'	88.6'	36.1'	62.3'	88.6'	36.1'	62.3'	88.6'	36.1'	62.3'	88.6'	
C	B	(11m)	B	(19m)	B	(27m)	B	(11m)	B	(19m)	B	(27m)	B	(11m)	B	(27m)
0	28.9'	17,600	55.4'	4,400	81.7'	700	28.9'	5,100			28.9'	17,200	55.4'	4,000	81.7'	700

- A :Boom length in feet
 B :Load radius in feet
 C :Loaded boom angle (°)
 D :Minimum boom angle (°) for indicated length (no load)

NOTE: The lifting capacity data stored in the LOAD MOMENT INDICATOR (AML-C) is based on the standard number of parts of line listed in the chart.
 Standard number of parts of line for rubber operation should be according to the following table.

Boom length in feet (meters)	36.1' (11m)	36.1' to 88.6' (11m to 27m)	Single top Jib
Number of parts of line	6	4	1



WARNING AND OPERATING INSTRUCTIONS FOR ON RUBBER LIFTING CAPACITIES

- Rated lifting capacities on rubber are in pounds and do not exceed 75 % of tipping loads as determined by SAE J765-Crane Stability Test Code.
- Rated lifting capacities shown in the chart are based on condition that crane is set on firm level surfaces with axle oscillation lockout applied. Those above bold lines are based on tire capacity and those below, on crane stability. They are based on actual load radius increased by tire deformation and boom deflection.
- If the axle oscillation lockout cylinders contain air, the axle will not be locked completely and rated lifting capacities may not be obtainable. Bleed the cylinders according to the operation safety and maintenance manual.
- Rated lifting capacities are based on proper tire inflation, capacity and condition. Damaged tires are hazardous to safe operation of crane.
- Tires shall be inflated to correct air pressure.
- Over front operation shall be performed within two degrees in front of chassis.
- On rubber lifting with "jib" is not permitted. Maximum permissible boom length is 88.6 ft. (27.0m).
- When making lift on rubber stationary, set parking brake.
- For creep operation, boom must be centered over front of machine, swing lock engaged, and load restrained from swinging. Travel slowly and keep the lifted load as close to the ground as possible, and especially avoid any abrupt steering, accelerating or braking.
- Do not operate the crane while carrying the load.
- Creep is motion for crane not to travel more than 200' (60 m) in any 30 minute period and to travel at the speed of less than 1 mph (1.6km/h).
- For creep operation, choose the drive mode and proper gear according to the road or working condition.

Tires	Air Pressure
29.5-25 22PR	60 psi (420 kPa)
29.5-25 28PR	64 psi (450 kPa)

WARNING AND OPERATING INSTRUCTIONS FOR USING THE LOAD MOMENT INDICATOR (AML-C)

1. When operating crane on outriggers:

Set P.T.O. switch to "ON".

Press the outrigger mode select key to register for the outrigger operation. Press the register key, then the outrigger mode indicative symbol changes from flashing to a solid light.

Press the lift mode select key to select the lift status that corresponds to the actual boom configuration.

Each time the lift mode select key is pressed, the status changes.

Press the register key to register the lift status, then the lift indicative symbol changes from flashing to a solid light.

when mounting and stowing jib, select the jib set status. (the jib state indicative symbol will be flashing.)

2. When operating crane on rubber:

Set P.T.O. switch to "ON".

Press the outrigger mode select key. The on-tire mode indicative symbol comes on. Each time the outrigger mode select key is pressed the status changes. Select the creep operation, the on-tire mode indicative symbol flicker.

Press the lift mode select key to register the boom or single top lift.

However, pay attention to the following.

(1) For stationary operation.

The front capacities are attainable only when the over front position symbol comes on. When the boom is more than 2 degrees from centered over front of chassis, 360 ° capacities are in effect.

- When a load is lifted in the front position and then swung to the side area, make sure the value of the LOAD MOMENT INDICATOR (AML-C) is below the 360 ° lifting capacity.

(2) For creep operation.

- The creep capacities are attainable only when boom is in the straight forward position of chassis and the over front position symbol is on. If boom is not in the straight forward position of chassis, never lift load.

3. A swing does not automatically stop even if the crane becomes overloaded.

4. During crane operation, make sure that the displays on front panel are in accordance with actual operating conditions.

5. The displayed values of LOAD MOMENT INDICATOR (AML-C) are based on freely suspended loads and make no allowance for such factors as the effect of wind, sudden stopping of loads, supporting surface conditions, inflation of tire, operating speed, side loads, etc.
For safe operation, it is recommended when extending and lowering boom or swinging, lifting loads shall be appropriately reduced.

6. LOAD MOMENT INDICATOR (AML-C) is intended as an aid to the operator. Under no condition should it be relied upon to replace use of capacity charts and operating instruction. Sole reliance upon LOAD MOMENT INDICATOR (AML-C) aids in place of good operating practice can cause an accident. The operator must exercise caution to assure safety.

GR-750XL Axle weight distribution chart

GVW 97,620		Pounds			Kilograms		
			Front	Rear	GVW	Front	Rear
Base machine			49,650	47,970	44,280	22,520	21,760
Remove:	1. 6.2ton (5.6metric ton) hook ball	-330	-470	140	-150	-214	64
	2. 75ton (68metric ton) hook block	-1,300	-2,310	1,010	-590	-1,048	458
	3. Top jib	-740	-805	65	-336	-365	29
	4. Base jib	-1,910	-3,270	1,360	-867	-1,483	616
	5. Auxiliary lifting sheave	-110	-300	190	-50	-137	87
	6. Counterweight (with Auxiliary hoist & wire rope)	-12,500	5,510	-18,010	-5,670	2,498	-8,168
Add:	75 ton (68metric ton) hook block (1,600lbs)	1,600	2,840	-1,240	726	1,290	-564

TADANO AMERICA CORPORATION

4242 West Greens Road

Houston, Texas, 77066 U.S.A.

PHONE: (281) 869-0030

FAX: (281) 869-0040

<http://www.tadanoamerica.com>

Form No. TAC-GR-750XL-2-00201-01132014